



SKINDICHT® ZS-M

SKINDICHT® ZS-M, PG 가 ,

PG 가 .

PG 가

DIN EN 60423
DIN IEC 62444

SKINDICHT® ZS-M-XL

ETIM 5: ETIM 5.0 Class-ID: EC000441
ETIM 5.0 :

ETIM 6: ETIM 6.0 Class-ID: EC000441
ETIM 6.0 Class :

:
: -60°C +200°C

가 VAT 가 가 .

(20.08.2024)



SKINDICHT® ZS-M

	(thread) , M1	(thread) , PG	/ PU
SKINDICHT® ZS-M			
52104330	12 x 1.5	7	100
52104340	16 x 1.5	9	100
52104010	16 x 1.5	11	100
52104360	20 x 1.5	11	100
52104370	20 x 1.5	13.5	100
52104380	20 x 1.5	16	50
52104400	25 x 1.5	21	50
52104410	32 x 1.5	29	25
52104420	40 x 1.5	36	10
52104430	50 x 1.5	42	10
52104440	63 x 1.5	48	10
SKINDICHT® ZS-M-XL			
52104335	12 x 1.5	7	100
52104345	16 x 1.5	9	100
52104365	20 x 1.5	11	100
52104375	20 x 1.5	13.5	100
52104385	20 x 1.5	16	50
52104405	25 x 1.5	21	50
52104415	32 x 1.5	29	25
52104425	40 x 1.5	36	10
52104435	50 x 1.5	42	10
52104445	63 x 1.5	48	10

(20.08.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16