



SKINDICHT® EKU-M

SKINDICHT® EKU-M,

가

DIN EN 60423

DIN IEC 62444

ETIM 5:

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 :

ETIM 6:

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class :

:

(RAL 7035)

Black (RAL 9005), UV-resistant

:

,

:

-40°C ~ +100°C

가 VAT

가 가 .

(24.08.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

SKINDICHT® EKU-M

	(thread) , M1	(thread) , M2	SW (mm)	/ PU
SKINDICHT® EKU-M				
52100300	12 x 1.5	16 x 1.5	20	100
52100301	16 x 1.5	20 x 1.5	24	100
52100302	20 x 1.5	25 x 1.5	29	100
52100303	25 x 1.5	32 x 1.5	36	50
52100304	32 x 1.5	40 x 1.5	46	25
52100305	40 x 1.5	50 x 1.5	55	10
52100306	50 x 1.5	63 x 1.5	68	10
SKINDICHT® EKU-M				
52100308	12 x 1.5	16 x 1.5	20	100
52100309	16 x 1.5	20 x 1.5	24	100
52100310	20 x 1.5	25 x 1.5	30	100
52100311	25 x 1.5	32 x 1.5	36	50
52100312	32 x 1.5	40 x 1.5	44	25
52100313	40 x 1.5	50 x 1.5	55	10
52100314	50 x 1.5	63 x 1.5	70	10

(24.08.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16