

SKINDICHT® MR-M ATEX

SKINDICHT® MR-M ATEX, , 가



O- 가

II / 2G+1D

DIN EN 60079-0
DIN EN 60079-7
DIN EN 60079-31

DIN EN 60423
DIN IEC 62444

ETIM 5:	ETIM 5.0 Class-ID: EC000441
	ETIM 5.0 :
ETIM 6:	ETIM 6.0 Class-ID: EC000441
	ETIM 6.0 Class :
:	CE 0637 Ex II 2G
	Ex eb IIC
	Ex II 1D Ex ta IIIC
	IECEx IBE 13.0028X



SKINDICHT® MR-M ATEX

:

:

:

O- : NBR

-30°C +90°C

가 VAT 가 가 .

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

SKINDICHT® MR-M ATEX

	(thread) , M1	(thread) , M2	(mm)	SW (mm)	Thread length D mm	Ø (mm)	/ PU
SKINDICHT® MR-M ATEX							
52104570	16 x 1.5	12 x 1.5	10.5	17	5	19.0	50
52104571	20 x 1.5	16 x 1.5	13	22	6	24.5	50
52104572	25 x 1.5	20 x 1.5	15	27	7	30.1	25
52104573	32 x 1.5	25 x 1.5	16.5	34	8	37.2	25
52104574	40 x 1.5	32 x 1.5	16.5	41	8	45.6	10
52104575	50 x 1.5	40 x 1.5	19.5	50	10	55.3	5
52104576	63 x 1.5	50 x 1.5	18.5	65	8.5	71.3	5