

E+D 가 SKINDICHT® RWV-M

E+D 가 SKINDICHT® RWV-M,

, 가



가

DIN EN 60423

DIN IEC 62444

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



E+D 가 SKINDICHT® RWV-M

: SKINDICHT® SM-M IP55.

For combination with other SKINDICHT® or SKINTOP® cable glands, we propose our SKINDICHT® RWV-M without incised sealing ring (E) and compression screw (D)

ETIM 5: ETIM 5.0 Class-ID: EC000441
ETIM 5.0 :

ETIM 6: ETIM 6.0 Class-ID: EC000441
ETIM 6.0 Class :

:
8 :
O- : NBR

가: IP 55
: -20°C +100°C

가 VAT 가 가 .

(24.04.2024)



E+D 가

SKINDICHT® RWV-M

| | Article designation / size | B in mm | Thread length D mm | K | L | Ø G | SW1 | Ø A1 | SW2 | Ø A2 | / PU |
|------------------------|----------------------------|---------|--------------------|---|------|-----|------|------|------|------|------|
| E+D 가 SKINDICHT® RWV-M | | | | | | | | | | | |
| 52107801 | M 12 x 1,5 | 21 | 11.5 | 5 | 20.5 | 8 | 14.0 | 16 | 17.0 | 18.9 | 25 |
| 52107811 | M 16 x 1,5 | 23 | 11.5 | 5 | 23.5 | 12 | 18.0 | 20 | 22.0 | 24.5 | 25 |
| 52107821 | M 20 x 1,5 | 28.5 | 12.5 | 5 | 28.5 | 15 | 22.0 | 24 | 27.0 | 30.1 | 25 |
| 52107831 | M 25 x 1,5 | 30 | 13.5 | 5 | 31 | 20 | 27.0 | 29 | 32.0 | 35.7 | 10 |
| 52107841 | M 32 x 1,5 | 36.5 | 13.5 | 5 | 33.5 | 27 | 34.0 | 33.5 | 41.0 | 45.6 | 10 |
| 52107851 | M 40 x 1,5 | 43 | 15.5 | 5 | 43 | 35 | 42.0 | 43 | 46.0 | 50.6 | 5 |

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16