

SKINTOP® MULTI

SKINTOP® MULTI, , 가



Lapp



가

4mm

AS-I BUS

(23.04.2024)



SKINTOP® MULTI

()
/
UV-, ozone- and oil-resistant

UL 50, UL 50E, CSA C22.2
UL 508A(:)
UL File No. E349737

24- (36 x 112 mm)

SKINTOP® MULTI

ETIM 5:	ETIM 5.0 Class-ID: EC000240
	ETIM 5.0 :
ETIM 6:	ETIM 6.0 Class-ID: EC000240
	ETIM 6.0 Class :
:	UL File No. E349737
	Fire behaviour acc. to UL94 V-2
	Hazard Level HL 2 acc. to EN 45545-2
:	
:	
:	
가:	IP 68
:	-30°C +110°C

가 VAT 가 가 .



SKINTOP® MULTI

	Article designation / size	.	x Ø /	/ PU
52220065	SKINTOP® MULTI Version 1	22	16 x 3-7 mm, 6 x 8-12 mm	1
52220073	SKINTOP® MULTI Version 2	21	5 x 2-6 mm, 8 x 4-8 mm, 3 x 5-9 mm, 2 x 8-12 mm, 1 x 12-16 mm, 2 x AS-I BUS / 2 x 2-4 mm	1
52220080	SKINTOP® MULTI 3	30	30 x 2-6 mm	1
52220085	SKINTOP® MULTI 4	11	8 x 8-12 mm, 2 x 12-16 mm, 1 x 16-20 mm	1
52220101	SKINTOP® MULTI Version 5	27	27 x 4-8 mm	1
52220104	SKINTOP® MULTI Version 6	24	10 x 2-6 mm, 8 x 4-8 mm, 4 x 7-11mm, 2 x 10-14mm	1

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

SKINTOP® MULTI



(23.04.2024)