



SKINTOP® GMP-GL-M

SKINTOP® GMP-GL-M, (borehole)

UL E79903

DIN EN 60423
DIN IEC 62444

UL UL SKINTOP® 가

ETIM 5:	ETIM 5.0 Class-ID: EC000940
	ETIM 5.0 :
ETIM 6:	ETIM 6.0 Class-ID: EC000940
	ETIM 6.0 Class :
:	가 (surface)
:	(RAL 7001)
	(RAL 7035)
	(RAL 9005), UV-
:	,
:	: -40°C +100°C
	: -20°C ~ +100°C

가 VAT 가 가 .

(23.08.2024)



SKINTOP® GMP-GL-M

	Article designation / size	SW (mm)	/ PU
SKINTOP® GMP-GL-M			
53119000	M 12 x 1,5	17	100
53119010	M 16 x 1,5	22	100
53119020	M 20 x 1,5	27	100
53119030	M 25 x 1,5	34	100
53119040	M 32 x 1,5	41	100
53119050	M 40 x 1,5	50	25
53119060	M 50 x 1,5	60	25
53119070	M 63 x 1,5	75	25
SKINTOP® GMP-GL-M			
53119100	M 12 x 1,5	17	100
53119110	M 16 x 1,5	22	100
53119120	M 20 x 1,5	27	100
53119130	M 25 x 1,5	34	100
53119140	M 32 x 1,5	41	100
53119150	M 40 x 1,5	50	25
53119160	M 50 x 1,5	60	25
53119170	M 63 x 1,5	75	25
SKINTOP® GMP-GL-M			
53119003	M 12 x 1,5	17	100
53119013	M 16 x 1,5	22	100
53119023	M 20 x 1,5	27	100
53119033	M 25 x 1,5	34	100
53119043	M 32 x 1,5	41	100
53119053	M 40 x 1,5	50	25
53119063	M 50 x 1,5	60	25
53119073	M 63 x 1,5	75	25

(23.08.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16