

EPIC® DATA M12D Screw termination

Can be assembled in the field: M12 data connector with screw connection, for assembly with sensor/actuator cables, different variants available.

가



Lapp



High stability thanks to impact-resistant polyamide.

The service-friendly screw connection makes assembly possible without a special tool, and is suitable for connections which need to be detached again.

When connected, protection class IP 67 can be achieved.

Available in different designs.

Can be used universally on machine interfaces for many applications in data and signal transmission.

Good oil and chemical resistance.

Field assembly Industrial Ethernet connector

M12 D-coded acc. to IEC61076-2-101

ETIM 5:

ETIM 5.0 Class-ID: EC001121

ETIM 5.0

:

(15.05.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



EPIC® DATA M12D Screw termination

ETIM 6:

ETIM 6.0 Class-ID: EC001121

ETIM 6.0 Class :

가:

IP 67

():

-25°C bis +85°C

:

brass gold plated CuZn / Au

:

brass gold plated CuZn / Au

가 VAT 가 가 .

(15.05.2024)



EPIC® DATA M12D Screw termination

	(mm)	(mm)
381166331	4	8
381166340	4	8
381166334	4	8
381166324	4	8

(15.05.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

EPIC® DATA M12D Screw termination



(15.05.2024)

©2024 Lapp Group - all rights reserved.
<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16