

# UNITRONIC® BUS PB FD P COMBI

PROFIBUS HYBRID

PROFIBUS-DP, PROFIBUS-FMS FIP

-40°C +80°C

LAPP KABEL STUTTGART UNITRONIC® BUS PB FD P COMBI



Lapp



PUR 가 ( )  
PROFIBUS-FMS FIP PROFIBUS-DP

PROFIBUS DP.(SIEMENS SIMATIC® NET, FIP 가 : DIN 19245 EN 50170 )

HYBRID: +  
: IEC 60332-1-2

:  
3 x 1.0 mm<sup>2</sup> (AWG18)

: PE

: PUR, (RAL 4001)

(24.04.2024)



# UNITRONIC® BUS PB FD P COMBI

ETIM 5:	ETIM 5.0 Class-ID: EC000830
	ETIM 5.0 Class- :
ETIM 6:	ETIM 6.0 Class-ID: EC000830
	ETIM 6.0 Class :
:	(800 Hz): max. 30 nF/km
:	( ) 100 V
:	Core/core: 600 V
..:	150 ± 15 Ohm
:	: -5°C to +50°C
	: -40°C +80°C

가 가 ( ) 가 .  
[www.lappkabel.de/en/cable-standradlengths](http://www.lappkabel.de/en/cable-standradlengths)  
 : 30 kg or 250 m,  
 . (e.g. 1 x 500 m or 5 x 100 m ).  
 SIMATIC® SIEMENS AG . FIP World FIP .  
 Lapp Kabel PROFIBUS user organisation (PNO)  
 가 VAT 가 가 .



# UNITRONIC® BUS PB FD P COMBI

		( ) x ( ) x (mm)	(mm)	(kg/km)	(kg/km)
UNITRONIC® BUS PB FD P COMBI					
2170227	UNITRONIC® BUS PB FD P COMBI	1 x 2 x 0.64 Ø + 3 x 1.0 mm <sup>2</sup>	10.1	59	125

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16