

UNITRONIC® BUS PB FD P HYBRID

PROFIBUS-DP, -FMS FIP , HYBRID: + . , (),
 -40°C +70°C



Lapp



PUR 가 ()
 PROFIBUS-FMS FIP , PROFIBUS-DP .

PROFIBUS DP.(SIEMENS SIMATIC® NET, FIP 가 : DIN 19245 EN 50170 ,)

HYBRID: +
 : IEC 60332-1-2

1x2x0.64: , 4x1.5(AWG16): ,

(24.04.2024)



UNITRONIC® BUS PB FD P HYBRID

: PE

: PUR, (RAL 4001)

ETIM 5:

ETIM 5.0 Class-ID: EC000830

ETIM 5.0 Class- :

ETIM 6:

ETIM 6.0 Class-ID: EC000830

ETIM 6.0 Class :

:

(800 Hz): max. 30 nF/km

:

() 100 V

:

() : 15 x

:

Core/core: 600 V

Core/screen: 600 V

::

150 ± 15 Ohm

:

: -30°C +60°C

: -40°C +70°C

, 가 가 . (.) 가 .
www.lappkabel.de/en/cable-standradlengths

: 30 kg or 250 m, . (e.g. 1 x 500 m or 5 x 100 m).

SIMATIC® SIEMENS AG . FIP World FIP .

Lapp Kabel PROFIBUS user organisation (PNO)

가 VAT 가 가 .

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



UNITRONIC® BUS PB FD P HYBRID

		() x () x (mm)	(mm)	(kg/km)	(kg/km)
UNITRONIC® BUS PB FD P HYBRID					
2170495	UNITRONIC® BUS PB FD P HYBRID	1 x 2 x 0.64 Ø + 4 x 1.5 mm ²	11.3	89	148

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16