

UNITRONIC® BUS PB FD P

PROFIBUS

PROFIBUS-DP, PROFIBUS-FMS FIP , , , -40°C +80°C



PROFIBUS-FMS FIP 가 PROFIBUS-DP
PUR 가 ()

PROFIBUS DP.(SIEMENS SIMATIC® NET, FIP 가 : DIN 19245 EN 50170 ,)
WTG() (,)

: IEC 60332-1-2

PNO
(A, PROFIBUS-DP):
93.75 kbit/s = 1200 m
187.5 kbit/s = 1000 m
500 kbit/s = 400 m
1.5 Mbit/s = 200 m
12.0 Mbit/s = 100 m

(23.12.2023)

UNITRONIC® BUS PB FD P

: (O2YS)
 :
 : PUR, (RAL 4001)

ETIM 5:	ETIM 5.0 Class-ID: EC000830
	ETIM 5.0 Class- :
ETIM 6:	ETIM 6.0 Class-ID: EC000830
	ETIM 6.0 Class :
:	(800 Hz): max. 30 nF/km
:	() 250 V
:	65 mm
:	/ : 1500 V
..	150 ± 15 Ohm
:	: -30°C +70°C
	: -40°C +80°C

, 가 가 . (.) 가 .
www.lappkabel.de/en/cable-standradlengths
 : 30 kg or 250 m,
 . (e.g. 1 x 500 m or 5 x 100 m).
 SIMATIC® SIEMENS AG . FIP World FIP .
 Lapp Kabel PROFIBUS user organisation (PNO)
 가 VAT 가 가 .



UNITRONIC® BUS PB FD P

		() x () x (mm)	(mm)	(kg/km)	(kg/km)
(,)-					
2170222	UNITRONIC® BUS PB FD P	1 x 2 x 0.64	8	30.1	64

(23.12.2023)

©2023 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16