

UNITRONIC® BUS PB 105

PROFIBUS

80°C

PROFIBUS-DP, -FMS und FIP
-30°C +105°C

가 가

LAPP KABEL STUTTGART UNITRONIC® BUS PB 105



Lapp



105°C

: IEC 60332-1-2

7-가 ,

: 0.64mm(AWG24)

: PP

:

: PVC, (RAL 4001)

ETIM 5:

ETIM 5.0 Class-ID: EC000830

ETIM 5.0 Class- :

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

UNITRONIC® BUS PB 105

ETIM 6:

ETIM 6.0 Class-ID: EC000830

ETIM 6.0 Class :

:	28.5 nF/km
:	. 100 V ()
:	: 45 mm (1)
:	: 65 mm
:	/ : 1500 V
:	/ : 1500 V
:	(3 - 20 MHz): 150 ± 15 Ohm
:	-30°C +105°C

가 가 . (.) 가 .
www.lappkabel.de/en/cable-standradlengths
 Lapp Kabel PROFIBUS user organisation (PNO)
 가 VAT 가 가 .



UNITRONIC® BUS PB 105

		() x () x (mm)	(mm)	(kg/km)	(kg/km)
2170630	UNITRONIC® BUS PB 105	1 x 2 x 0.64	8	30.1	72

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16