

UNITRONIC® BUS PB ARM

가 가 PROFIBUS

PROFIBUS-DP, PROFIBUS-FMS

FIP

가 .

-40°C bis +70°C



EMC

PROFIBUS-DP FIP
PROFIBUS DP.(SIEMENS SIMATIC® NET, FIP

가

: DIN 19245 EN 50170

2

)

: IEC 60332-1-2

UV-

() : , O2Y(S)
;

: PVC

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02 03.16

UNITRONIC® BUS PB ARM

ETIM 5:	ETIM 5.0 Class-ID: EC000830
	ETIM 5.0 Class- :
ETIM 6:	ETIM 6.0 Class-ID: EC000830
	ETIM 6.0 Class :
:	(800 Hz): max. 30 nF/km
:	() 100 V
:	: 7.5 x
	: 3.5 x , 1
:	3600 V DC (3)
..	150 ± 15 Ohm
:	-40°C +70°C

, 가 가 . (.) 가 .
 www.lappkabel.de/en/cable-standradlengths
 : ≤ 30 kg or ≤ 250 m,
 . (e.g. 1 x 500 m or 5 x 100 m).
 SIMATIC® SIEMENS AG . FIP World FIP .
 Lapp Kabel PROFIBUS user organisation (PNO)
 가 VAT 가 가 .



UNITRONIC® BUS PB ARM

		() x () x (mm)	(mm)	(kg/km)	(kg/km)
2170247	UNITRONIC® BUS PB ARM	1 x 2 x 0.65	11.1	86.9	131

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16