

UNITRONIC® BUS PB BURIAL FC

/ PROFIBUS
 PROFIBUS-DP, PROFIBUS-FMS FIP , UV . -40°C bis +60°C



Lapp



가



(FC)
 (), UV-
 PROFIBUS-FMS FIP PROFIBUS-DP .

PROFIBUS DP.(SIEMENS SIMATIC® NET, FIP 가 : DIN 19245 EN 50170 ,)

(24.04.2024)

UNITRONIC® BUS PB BURIAL FC

PE

: (O2YS)
 :
 : PVC, RAL(4001), : 8.0 mm
 : PE, RAL(9005), : 10.8 mm

ETIM 5: ETIM 5.0 Class-ID: EC000830
ETIM 5.0 Class- :

ETIM 6: ETIM 6.0 Class-ID: EC000830
ETIM 6.0 Class :

: (800 Hz): max. 30 nF/km
 : () 100 V
 : : 3.5 x , 1
 : : 7.5 x
 : 3600 V DC (3)
 : : 150 ± 15 Ohm
 : -40 °C +60 °C

, 가 가 . (.) 가 .
 www.lappkabel.de/en/cable-standradlengths
 : 30 kg or 250 m,
 . (e.g. 1 x 500 m or 5 x 100 m).
 SIMATIC® SIEMENS AG . FIP World FIP .
 Lapp Kabel PROFIBUS user organisation (PNO)
 가 VAT 가 가 .



UNITRONIC® BUS PB BURIAL FC

		() x () x (mm)	(mm)	(kg/km)	(kg/km)
2170323	UNITRONIC® BUS PB BURIAL FC	1 x 2 x 0.64	10.8	26	115

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16