

UNITRONIC® BUS PB FRNC FC

FRNC PROFIBUS

UL/CSA

-30°C bis +80°C

PROFIBUS-DP, -FMS

FIP

()

FRNC =

-

가

-

가

-

LAPP KABEL STÜTGART UNITRONIC® BUS PB FRNC FC 



Lapp



PROFIBUS-FMS
PUR

FIP
가
(FC)

PROFIBUS-DP

()

()

(24.04.2024)

UNITRONIC® BUS PB FRNC FC

Vertical Tray Flame Test according to UL 1685

PNO
 (A, PROFIBUS-DP):
 93.75 kbit/s = 1200 m
 187.5 kbit/s = 1000 m
 500 kbit/s = 400 m
 1.5 Mbit/s = 200 m
 12.0 Mbit/s = 100 m

UL/CSA

: PE
 (),
 : PUR, (RAL 4001)

ETIM 5:	ETIM 5.0 Class-ID: EC000830
	ETIM 5.0 Class- :
ETIM 6:	ETIM 6.0 Class-ID: EC000830
	ETIM 6.0 Class :
:	UL/CSA (CM)
:	28.5 nF/km
:	() 250 V
:	80 mm
:	/ : 1500 V
:	/ : 1500 V
::	(3 - 20 MHz): 150 ± 15 Ohm
:	-30°C +80°C

, 가 가 . (.) 가 .
www.lappkabel.de/en/cable-standradlengths
 : 30 kg or 250 m,
 . (e.g. 1 x 500 m or 5 x 100 m).
 Lapp Kabel PROFIBUS user organisation (PNO)
 가 VAT 가 가 .



UNITRONIC® BUS PB FRNC FC

		() x () x (mm)	(mm)	(kg/km)	(kg/km)
2170996	UNITRONIC® BUS PB FRNC FC	1 x 2 x 0.64	8	30.1	74

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16