

# UNITRONIC® BUS PB Y 7-W FC BK

가 UV PROFIBUS

PROFIBUS-DP, -FMS FIP , (FC) UV -40°C  
+80°C .



Lapp



가



(FC)  
7-W: 7가 (7 ),  
PROFIBUS-FMS FIP PROFIBUS-DP .

PROFIBUS DP.(SIEMENS SIMATIC® NET, FIP 가 : DIN 19245 EN 50170 , )

UV

(23.04.2024)



# UNITRONIC® BUS PB Y 7-W FC BK

7-가 ,  
 : (O2YS)  
 : PVC, RAL(9005)

ETIM 5:	ETIM 5.0 Class-ID: EC000830
	ETIM 5.0 Class- :
ETIM 6:	ETIM 6.0 Class-ID: EC000830
	ETIM 6.0 Class :
:	(800 Hz): max. 30 nF/km
:	( ) 250 V
:	: 8 x
	: 15 x
:	/ : 1500 V
	/ : 1500 V
::	150 ± 15 Ohm
:	: -10°C +70°C
	: -40°C +80°C

가 가 ( . ) 가 .  
 www.lappkabel.de/en/cable-standradlengths  
 : 30 kg or 250 m,  
 . (e.g. 1 x 500 m or 5 x 100 m ).  
 SIMATIC® SIEMENS AG . FIP World FIP .  
 Lapp Kabel PROFIBUS user organisation (PNO)  
 가 VAT 가 가 .



UNITRONIC® BUS PB Y 7-W FC BK

		( ) x ( ) x (mm)	(mm)	(kg/km)	(kg/km)
2170310	UNITRONIC® BUS PB Y 7-W FC BK	1 x 2 x 0.64	7.8	30.1	80

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16