

UNITRONIC® BUS PB Yv

/

PVC

PROFIBUS

PROFIBUS-DP

FMS

FIP. BUS

, UV

,

,

-40°C bis +80°C



Lapp



가



(

), UV-

PROFIBUS-FMS

FIP

PROFIBUS-DP

.

PROFIBUS DP.(SIEMENS SIMATIC® NET, FIP

가

:

DIN 19245

EN 50170

,

)

PVC

UNITRONIC® BUS PB Yv

: (O2YS)
:
(): PVC,

ETIM 5: ETIM 5.0 Class-ID: EC000830
ETIM 5.0 Class- :
ETIM 6: ETIM 6.0 Class-ID: EC000830
ETIM 6.0 Class :
: (800 Hz): max. 30 nF/km
: () 250 V
: : 75mm
: 150 mm
: / : 1500 V
/ : 1500 V
.: 150 ± 15 Ohm
: : -5°C to +50°C
: -40°C +80°C

, 가 가 . (.) 가 .
www.lappkabel.de/en/cable-standradlengths
: ≤ 30 kg or ≤ 250 m,
(e.g. 1 x 500 m or 5 x 100 m).
SIMATIC® SIEMENS AG . FIP World FIP .
Lapp Kabel PROFIBUS user organisation (PNO)
가 VAT 가 가 .



UNITRONIC® BUS PB Yv

		() x () x (mm)	(mm)	(kg/km)	(kg/km)
2170223	UNITRONIC® BUS PB Yv	1 x 2 x 0.64	9.4	30.1	106