

UNITRONIC® BUS PB Yv

/ PVC PROFIBUS
 PROFIBUS-DP FMS FIP. BUS , UV , , -40°C bis +80°C



Lapp



가



(), UV-
 PROFIBUS-FMS FIP PROFIBUS-DP .

PROFIBUS DP.(SIEMENS SIMATIC® NET, FIP 가 : DIN 19245 EN 50170 ,)

PVC

(24.04.2024)

UNITRONIC® BUS PB Yv

: (O2YS)
 :
 (): PVC,

| | |
|---------|-----------------------------|
| ETIM 5: | ETIM 5.0 Class-ID: EC000830 |
| | ETIM 5.0 Class- : |
| ETIM 6: | ETIM 6.0 Class-ID: EC000830 |
| | ETIM 6.0 Class : |
| : | (800 Hz): max. 30 nF/km |
| : | () 250 V |
| : | : 75mm |
| | : 150 mm |
| : | / : 1500 V |
| | / : 1500 V |
| :: | 150 ± 15 Ohm |
| : | : -5°C to +50°C |
| | : -40°C +80°C |

, 가 가 . (.) 가 .
 www.lappkabel.de/en/cable-standradlengths
 : 30 kg or 250 m,
 . (e.g. 1 x 500 m or 5 x 100 m).
 SIMATIC® SIEMENS AG . FIP World FIP .
 Lapp Kabel PROFIBUS user organisation (PNO)
 가 VAT 가 가 .



UNITRONIC® BUS PB Yv

| | | () x () x (mm) | (mm) | (kg/km) | (kg/km) |
|---------|----------------------|---------------------|------|---------|---------|
| 2170223 | UNITRONIC® BUS PB Yv | 1 x 2 x 0.64 | 9.4 | 30.1 | 106 |

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16