

EPIC® DATA PB Sub-D FC

PROFIBUS

PROFIBUS Sub-D , , LED / , ()

35°/90°/180°

2 Sub-D (90 ° 180 °)
LED 가



Lapp



Fast Connect ('FC')
/ ac

LED:
- (),
- (),
- ()

12 Mbit/s 가

(24.04.2024)

EPIC® DATA PB Sub-D FC

12,5 mA (LED 35 mA)
4,75 ~ 5,25 V DC ()
가 "ON" , 가

IEC 61158, IEC 61784
UL File No. E331560

D-Sub , 9 , 4-40 UNC
(EMC)

:

8mm

가

/

: Sub-D , 9

LED

:

- (),

- (),

- ()

ETIM 5:

ETIM 5.0 Class-ID: EC001132

ETIM 5.0 : D-Sub-

ETIM 6:

ETIM 6.0 Class-ID: EC001132

ETIM 6.0 Class : D-Sub

:

95 mm x 70 mm x 17 mm - 35°

72 mm x 40 mm x 17 mm - 90°

70 mm x 35 mm x 17 mm - 180°

(LxWxH)

:

가:

IP 20

:

150 Ω

:

Sub-D , 9

PROFIBUS FC

, Ø 0.64 mm

가

:

: -25°C~+85°C

*The max. temperature for UL is 60 °C

가

VAT

가

가

.

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

EPIC® DATA PB Sub-D FC

		PG-	LED
, 7 19 90 °			
21700502	ED-PB-90-FC	no	no
21700501	ED-PB-90-PG-FC	yes	no
21700547	ED-PB-90-LED-FC	no	yes
21700546	ED-PB-90-PG-LED-FC	yes	yes
, 7 19 180 (AX)			
21700544	ED-PB-AX-FC	no	no

EPIC® DATA PB Sub-D FC



(24.04.2024)