

UNITRONIC® BUS PA

가 PROFIBUS

: -30 °C bis + 80 °C

PA =
UL/CSA CMG 가



Lapp



FC (Fast Connect)

UV-

= 31.25 kbit/s. RS485 가 1.5 Mbit/s
가 (,)
: "UNITRONIC® BUS Cables"

: IEC 60332-1-2

(23.04.2024)



UNITRONIC® BUS PA

PROFIBUS® PA PROFIBUS® DP PROFIBUS® FMS EN 50170

IEC 61158-2

PROFIBUS-PA

FC :

UL/CSA (CMG / PLTC)

UNITRONIC® BUS PA (BU/BK)

UNITRONIC® BUS PA FC (BU/BK) , PVC , : (" 가) , : (: IDC ())
) 가 , UL/CSA CMG ' " 가 : IDC ()

ETIM 5:

ETIM 5.0 Class-ID: EC000830

ETIM 5.0 Class- :

ETIM 6:

ETIM 6.0 Class-ID: EC000830

ETIM 6.0 Class :

: () 250 V
: (): . 44 ohm/km
: : 10 x
: / : 1500 V
.: 100 ± 20 Ohm
: :
-30°C +80°C
: -5°C ~ +90°C

가 가 . (.) 가 .
www.lappkabel.de/en/cable-standradlengths
: 30 kg or 250 m,
(e.g. 1 x 500 m or 5 x 100 m).

SIMATIC® Siemens AG

가 VAT 가 가 .



UNITRONIC® BUS PA

		in mm /	(mm)	(kg/km)	(kg/km)
2170234	UNITRONIC® BUS PA (BU)	1 x 2 x 1.3	8	45	84
2170235	UNITRONIC® BUS PA (BK)	1 x 2 x 1.3	8	45	84
- UL/CSA CMG					
2170334	UNITRONIC® BUS PA FC (BU)	1 x 2 x 1	8	45.5	103
2170335	UNITRONIC® BUS PA FC (BK)	1 x 2 x 1	8	45.5	103

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



UNITRONIC® BUS PA



(23.04.2024)

©2024 Lapp Group - all rights reserved.
<http://lappkorea.lappgroup.com>
data sheet

PN 0456 / 02_03.16