

# UNITRONIC® BUS LD

PVC 가  
 . Modbus, SUCOnet, Modulink, VariNet. , UL , DIN 47100. : -40 ° C +  
 80 ° C

LD LAPP



Lapp



RS485 / RS422

ModBUS, SUCOnet P, Modulink P, VariNet-P) BUS

BUS ( )  
 9.6-93.75 kbit/s = 1200m  
 187.5 kbit/s = . 1,000 m  
 500 kbit/s = max. 400 m

UNITRONIC®BUS LD A: UL ; UL 444 CSA C22.2 No.214-02 UL/CSA CMX

IEC 60332-1-2

(23.04.2024)

# UNITRONIC® BUS LD

, , 7  
 : PE  
 DIN 47100  
 : PVC, (RAL 4001)

ETIM 5:	ETIM 5.0 Class-ID: EC000830
	ETIM 5.0 Class- :
ETIM 6:	ETIM 6.0 Class-ID: EC000830
	ETIM 6.0 Class :
:	Flexible use: 10 x outer diameter
:	( ) 250 V
:	( ): . 186 ohm/km
:	: 8 x
:	/ : 1500 V
..	100 - 120 Ohm
:	: -40°C +80°C
	: -5°C +70°C

, 가 가 . ( . ) 가 .  
[www.lappkabel.de/en/cable-standradlengths](http://www.lappkabel.de/en/cable-standradlengths)  
 : 30 kg or 250 m,  
 . (e.g. 1 x 500 m or 5 x 100 m ).  
 Modbus Modbus-IDA Organisation .. SUCOnet P Moeller Group . Modulink P  
 Weidmüller GmbH & Co. . VariNet Pepperl+Fuchs GmbH .

가 VAT 가 가 .



# UNITRONIC® BUS LD

		mm <sup>2</sup> /	(mm)	(kg/km)	(kg/km)
2170203	UNITRONIC® BUS LD	1 x 2 x 0.22	5.7	18	37
2170204	UNITRONIC® BUS LD	2 x 2 x 0.22	7.1	28	45
2170205	UNITRONIC® BUS LD	3 x 2 x 0.22	7.2	37	72
UL/CSA CMX					
2170803	UNITRONIC® BUS LD A	1 x 2 x 0.22	5.7	18	39