



UNITRONIC® EB CY (TP)

가

UNITRONIC® EB CY (TP): PVC , DIN 47100 , , , , EN
60079-14/VDE 0165-1

-i-가

CPR: www.lappkabel.com/cpr



- (TP) (Crosstalk)

EMC-
()

IEC 60079-14:2013/EN 60079-14:2014/VDE 0165-1:2014, 16.2.2 (i-)
: IEC 60332-1-2

VDE 0812

가

PVC

(23.12.2023)

UNITRONIC® EB CY (TP)

TP

PVC : (RAL 5015)

ETIM 5: ETIM 5.0 Class-ID: EC000104
ETIM 5.0

ETIM 6: ETIM 6.0 Class-ID: EC000104
ETIM 6.0 Class :

: DIN 47100, T9

: C/C approx. 100 nF/km

: C/S approx. 140 nF/km

: 0.65 mH/km

: IEC 60228 Cl. 5 ,

: : 15 x

: 6 x

: 2500 V

: : -5°C ~ +70°C

: -40°C +80°C

가 가 () 가
www.lappkabel.de/en/cable-standradlengths
: 30 kg or 250 m,
(e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .



UNITRONIC® EB CY (TP)

	(mm ²) /	(mm)	(kg/km)	(kg/km)
UNITRONIC® EB CY (TP)				
0012620	2 x 2 x 0.75	8.7	58	106
0012621	3 x 2 x 0.75	9.6	84	140
0012622	4 x 2 x 0.75	10.9	108	179
0012624	6 x 2 x 0.75	12.3	146	246
0012626	10 x 2 x 0.75	16.1	220	392

(23.12.2023)

©2023 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16