



UNITRONIC® LiYCY-CY

가

UNITRONIC® LiYCY-CY: PVC , DIN 47100 , , , , ,



가 가

- 가

: IEC 60332-1-2

VDE 0812

PVC 가

PVC

Outer sheath made of PVC

(23.04.2024)

UNITRONIC® LiYCY-CY

Outer sheath colour: grey (similar to pebble grey/ RAL 7032)

| | |
|---------|---|
| ETIM 5: | ETIM 5.0 Class-ID: EC000104 ETIM 5.0 |
| ETIM 6: | ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class : |
| : | DIN 47100, T9 |
| : | 230 nF/km |
| : | 0.2 mH/km |
| : | , 가 |
| : | : 15 x |
| : | : 7.5 x |
| : | : -5°C ~ +70°C |
| : | : -40°C +80°C |

가 가 (.) 가 .
www.lappkabel.de/en/cable-standradlengths
: 30 kg or 250 m,
(e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .



UNITRONIC® LIYCY-CY

| | (CORE) / (mm ²) | (mm) | [kg/km] | [kg/km] |
|---------------------|-----------------------------|------|---------|---------|
| UNITRONIC® LIYCY-CY | | | | |
| 0032302 | 2 x 0.25 | 6.9 | 41.5 | 69 |
| 0032303 | 3 x 0.25 | 7.2 | 53 | 106 |
| 0032304 | 4 x 0.25 | 7.8 | 65 | 130 |
| 0032305 | 5 x 0.25 | 8.5 | 78 | 161 |

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16