

UNITRONIC® LiYD11Y

() PUR

UNITRONIC® LiYD11Y: PUR , , PVC , DIN 47100, 가 ,
-5°C ~ +70°C,



PUR

, ,

가 , , ,
가

PUR , ,

UV-
IEC 60332-2-2 가 : "UNITRONIC® SPIRAL"

(25.04.2024)

UNITRONIC® LiYD11Y

VDE 0812

PVC

:

PUR

: (RAL 9005)

ETIM 5:

ETIM 5.0 Class-ID: EC000104
ETIM 5.0

ETIM 6:

ETIM 6.0 Class-ID: EC000104
ETIM 6.0 Class :

:

DIN 47100 , T9

:

C/C approx. 140 nF/km

C/S approx. 150 nF/km

:

0.65 mH/km

:

,

:

: 10 x

: 6 x

:

: -5°C ~ +70°C

: -40°C +80°C

, 가 가 . (.) 가 .
www.lappkabel.de/en/cable-standradlengths
: ≤ 30 kg or ≤ 250 m,
(e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .

(25.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

UNITRONIC® LIYD11Y

	(CORE) / (mm ²)	(mm)	[kg/km]	[kg/km]
UNITRONIC® LIYD11Y				
0033202	2 x 0.14	4.1	9.6	20
0033203	3 x 0.14	4.3	11	25
0033204	4 x 0.14	4.5	12	27
0033205	5 x 0.14	4.8	14.4	33
0033206	6 x 0.14	5.5	17.6	38
0033207	7 x 0.14	5.9	21.5	41
0033212	12 x 0.14	7.2	33.2	62
0033218	18 x 0.14	8	44.2	83
0033302	2 x 0.25	4.7	11.8	25
0033303	3 x 0.25	5.3	15.6	31
0033304	4 x 0.25	5.6	18.2	36
0033305	5 x 0.25	6	21.4	42
0033306	6 x 0.25	6.8	26.1	49
0033307	7 x 0.25	7.3	27.8	53
0033312	12 x 0.25	8.4	48.1	81
0033318	18 x 0.25	9.7	69	117