

# UNITRONIC® LiYY (TP)

( ) DIN 47100

UNITRONIC® LiYY (TP): PVC DIN 47100 , , 0.34mm<sup>2</sup> Maxi TERMI-POINT®, , ,

TP =  
CPR: [www.lappkabel.com/cpr](http://www.lappkabel.com/cpr)



- (TP) (Crosstalk )

. 가  
: IEC 60332-1-2

VDE 0812

가  
PVC  
TP  
Outer sheath made of PVC  
Outer sheath colour: grey (similar to pebble grey/ RAL 7032)

ETIM 5:

ETIM 5.0 Class-ID: EC000104

(23.04.2024)

# UNITRONIC® LiYY (TP)

ETIM 6:

:  
:  
:  
:  
:  
:  
:

ETIM 5.0

ETIM 6.0 Class-ID: EC000104

ETIM 6.0 Class :

DIN 47100, T9

120 nF/km

0.65 mH/km

: 10 x

: 4 x

: -5°C ~ +70°C

: -40°C +80°C

, 가 가 . ( . ) 가 .  
www.lappkabel.de/en/cable-standradlengths  
: 30 kg or 250 m,  
(e.g. 1 x 500 m or 5 x 100 m ).

가 VAT 가 가 .

(23.04.2024)



UNITRONIC® LiYY (TP)

	(mm <sup>2</sup> ) /	(mm)	(kg/km)	(kg/km)
UNITRONIC® LiYY (TP)				
0035101	2 x 2 x 0.14	4.5	5.4	25.5
0035102	3 x 2 x 0.14	5	8	32
0035103	4 x 2 x 0.14	5.6	10.7	38.5
0035104	5 x 2 x 0.14	5.8	13.4	45.5
0035105	6 x 2 x 0.14	6.3	16.1	51
0035108	10 x 2 x 0.14	8.1	26.9	77.5
0035110	12 x 2 x 0.14	8.3	32.3	94.5
0035113	16 x 2 x 0.14	9.2	43	110.5
0035160	2 x 2 x 0.25	5.7	9.6	38
0035161	3 x 2 x 0.25	6.3	14.4	48
0035162	4 x 2 x 0.25	7	19.2	59
0035163	6 x 2 x 0.25	7.9	28.8	80
0035164	8 x 2 x 0.25	9.3	38.4	98
0035170	2 x 2 x 0.5	7.3	19.2	72
0035171	3 x 2 x 0.5	8.1	28.8	83
0035172	4 x 2 x 0.5	8.8	38.4	115
0035174	8 x 2 x 0.5	12.3	76.8	206
0035175	10 x 2 x 0.5	13.3	96	247

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16