

# UNITRONIC® PUR CP (TP)

PUR 가  
UNITRONIC® PUR CP (TP): PUR , PVC DIN 47100 , , , ,

TP =



PUR , PUR

- (TP) (Crosstalk )

PUR

(26.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16

# UNITRONIC® PUR CP (TP)

UV-  
: IEC 60332-1-2

VDE 0812

PVC  
TP  
PUR  
: (RAL 7032)

ETIM 5: ETIM 5.0 Class-ID: EC000104  
ETIM 5.0

ETIM 6: ETIM 6.0 Class-ID: EC000104  
ETIM 6.0 Class :

: DIN 47100, T9

: C/C: 120nF/km

: C/S: 160nF/km

: 0.65 mH/km

: : 15 x  
: 6 x

: : -5°C ~ +70°C

: : -40°C +80°C

가 가 ( ) 가  
: [www.lappkabel.de/en/cable-standradlengths](http://www.lappkabel.de/en/cable-standradlengths)  
30 kg or 250 m,  
(e.g. 1 x 500 m or 5 x 100 m ).

가 VAT 가 가 .

(26.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16



# UNITRONIC® PUR CP (TP)

	(mm <sup>2</sup> ) /	(mm)	(kg/km)	(kg/km)
UNITRONIC® PUR CP (TP)				
0032850	2 x 2 x 0.25	6.3	28	54
0032851	3 x 2 x 0.25	7.1	40	66
0032852	4 x 2 x 0.25	7.6	45	81
0032854	6 x 2 x 0.25	8.5	70	115
0032860	2 x 2 x 0.5	7.9	48	93
0032861	3 x 2 x 0.5	8.7	74	129
0032862	4 x 2 x 0.5	9.4	82	146
0032864	6 x 2 x 0.5	11.1	110	198

(26.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16