

UNITRONIC® FD

Highly flexible cable for power chain use

UNITRONIC® FD: PVC , / , / 2 ~ 8m , / ,



()

가

, ,

: IEC 60332-1-2

2 8 /

VDE 0812

For travel distances up to 10 m

: 가 T3

PVC

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

UNITRONIC® FD

PVC

: (RAL 7001)

ETIM 5:

ETIM 5.0 Class-ID: EC000104

ETIM 5.0

ETIM 6:

ETIM 6.0 Class-ID: EC000104

ETIM 6.0 Class :

:

DIN 47100, T9

:

C/C: approx. 100 nF/km

:

0.65 mH/km

:

,

:

: 5 x

: 3 x

:

1500 V

:

: -5°C

+70°C

: -40°C

+80°C

,

가

가

.

(.)

가

.

www.lappkabel.de/en/cable-standradlengths

: ≤ 30 kg or ≤ 250 m,

. (e.g. 1 x 500 m or 5 x 100 m).

가

VAT

가

가

.

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

UNITRONIC® FD

	(CORE) / (mm ²)	(mm)	(kg/km)	(kg/km)
UNITRONIC® FD				
0027841	3 x 0.14	3.9	4.2	26
0027842	4 x 0.14	4.2	5.6	31
0027843	5 x 0.14	4.5	7	35
0027844	7 x 0.14	5.1	9.8	50
0027845	10 x 0.14	6.1	14	63
0027846	14 x 0.14	6.2	19.6	77
0027847	18 x 0.14	6.8	25.2	91
0027848	25 x 0.14	8.3	35	125
0027855	2 x 0.25	4.3	5	27
0027856	3 x 0.25	4.5	7.5	33
0027857	4 x 0.25	4.9	10	40
0027858	5 x 0.25	5.3	12.5	45
0027859	7 x 0.25	6.1	17.5	59
0027860	10 x 0.25	7.4	25	75
0027861	14 x 0.25	7.5	35	108
0027863	18 x 0.25	8.5	45	130
0027865	25 x 0.25	10.4	62.5	178
0027870	2 x 0.34	4.7	6.8	30
0027871	3 x 0.34	5	10.2	43
0027872	4 x 0.34	5.4	13.6	57
0027873	5 x 0.34	5.9	17	65
0027874	7 x 0.34	6.8	23.8	85
0027875	10 x 0.34	8.5	34	117
0027876	14 x 0.34	8.6	47.6	151
0027877	18 x 0.34	9.7	61.2	182
0027878	25 x 0.34	11.9	85	250