

EPIC® POWER M12 60V

M12 POWER

M12 , 가 , / , / , 0.75-1,5 mm²

DC - 60VDC / 12A



Lapp



M12
M12 T

(28.02.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

EPIC® POWER M12 60V

‘ ‘ ‘
,

Robust M12 circular connector with screw connection and knurled screw

UL : E249137

4 : (1), (2), (3), (4)

: 0,75 mm² - 1.5 mm² (AWG 18 - AWG 16)

ETIM 5:

ETIM 5.0 Class-ID: EC002062

ETIM 5.0 :

ETIM 6:

ETIM 6.0 Class-ID: EC002062

ETIM 6.0 Class :

:

: CuZn : Au ()

(knurl) : , : PA

가:

IP 67

():

/
-40°C~+85°C

(-)

:

T - Power

(A):

12 A

가 VAT 가 가 .

(28.02.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

EPIC® POWER M12 60V

		Design	/	Cable diameter in mm	(V)	PU
22262010	AB-C4-M12MST-PG11		4	8 - 10	60	1
22262012	AB-C4-M12MAT-PG11		4	8 - 10	60	1
22262011	AB-C4-M12FST-PG11		4	8 - 10	60	1
22262013	AB-C4-M12FAT-PG11		4	8 - 10	60	1

EPIC® POWER M12 60V



(28.02.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16