

## UNITRONIC® SENSOR M12-M8

M12 (M8 )

How convenient! The PVC patch cable, which can be used universally for data and signal transmission, is already assembled on both sides. Not only that, but connecting with the mating connector on the M8 side is now even quicker and completely tool-free thanks to the snap-in function. In other words, push on instead of screwing on.



Lapp



The patch cable assembled on both sides saves time during installation and reduces or eliminates the potential for errors during on-site assembly.

The snap-in connector M8 allows quick, tool-free connection to the mating connector (no screwing necessary, pushing is enough). Snap-in function specifically supports maintenance and cleaning work.

Compact dimensions enable easy integration into the machine concept.

Can be used universally on machine interfaces for many applications in data and signal transmission.

Usable in dry, damp and wet environments.

The PVC outer sheath is resistant to acids and alkalis, and to oil to a limited degree.

Suitable for medium mechanical stress.

ETIM 5:

ETIM 5.0 Class-ID: EC001855

ETIM 5.0 Class: -

ETIM 6:

ETIM 6.0 Class-ID: EC001855

ETIM 6.0 Class :

가:

IP 65 / IP 67

( ):

/  
-25°C +80°C

:

A-Standard

(A):

3 A

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16



# UNITRONIC® SENSOR M12-M8

가 가 . ( . ) 가 .  
가 VAT 가 가 .  
UL-Zertifizierungen sind dem Datenblatt zu entnehmen

(24.04.2024)



# UNITRONIC® SENSOR M12-M8

44429471
44429472
44429473

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16