

## EPIC® POWER M12K Screw termination

This compact M12 connector with PE contact comes into play if you want more power. It is used to supply power to three-phase motors (630 V, 12 A per contact). The K-coding prevents incorrect plugging with other connectors.



The service-friendly screw connection makes assembly possible without a special tool, and is suitable for connections which need to be detached again.

Available in different designs.

High stability thanks to impact-resistant polyamide.

Powerful up to 12 A despite extremely space-saving size for the tightest of spaces.

Mechanical K-coding of the mating face prevents mismatching with mating connector.

Good oil and chemical resistance.

For connecting three-phase motors with up to 7.5 kW.

For power supply connection of devices and machines in various applications.

ETIM 5:

ETIM 5.0 Class-ID: EC002635

ETIM 5.0 class : ( )

ETIM 6:

ETIM 6.0 Class-ID: EC002635

ETIM 6.0 Class : ( )

(V):

630 V

:

6 kV

(A):

12 A

:

3

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16

## EPIC® POWER M12K Screw termination

/ : 4 + PE  
: : 0.5 - 2.5 mm<sup>2</sup>

가: IP 67  
: 100  
: -25°C ... +85°C

가 VAT 가 가 .

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16

# EPIC® POWER M12K Screw termination

	Version	Version		Clamping range min	Clamping range max			
381166314			5	8	12	Au	M12	4+PE
381166312			5	8	12	Au	-	4+PE
381166311			5	8	12	Au	-	4+PE
381166315			5	8	12	Au	-	4+PE

(24.04.2024)

## EPIC® POWER M12K Screw termination



(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16