

EPIC® H-A 16

400V H-A

400V

Made in Germany



400V

(22.02.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

EPIC® H-A 16

PH1

Railway applications

- Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL3

ETIM 5:

ETIM 5.0 Class-ID: EC000438

ETIM 5.0 class :

ETIM 6:

ETIM 6.0 Class-ID: EC000438

ETIM 6.0 Class-Description: Contact insert for industrial connectors

(V):

IEC: 400 V

UL: 600 V

CSA: 600 V

:

4 kV

(A):

IEC: 16 A

UL: 14 A

CSA: 16 A

:

3

:

UL94 V-0

:

1.5 - 4 mohm

:

/ :

16 + PE

:

: 0.5 - 2.5 mm²

(mm):

8

:

PC,

:

500

VDE-

:

: VDE-REG.

: B437

UL-

:

UL

: E75770

:

-40°C ~ +120°C

가

VAT

가

가 .

(22.02.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



EPIC® H-A 16

	Article description	Contact type			/ PU
H-A 16					
10530000	H-A 16 SS		yes	1 - 16	5
10531000	H-A 16 BS		yes	1 - 16	5
10532000	H-A 16 SS		-	1 - 16	5
10533000	H-A 16 BS		-	1 - 16	5