



# EPIC® H-B 16 TGB

H-B.

2

가  
NEMA 250, UL50E: 12, 4 (latched)



Lapp



2 가

(22.07.2024)

# EPIC® H-B 16 TGB

, low

neck /

ETIM 5:

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 class :

ETIM 6:

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

:

: - ,

: -

: NBR

가:

IP 65 (latched)

VDE- :

: VDE-REG. : B437

UL- :

UL : E75770

:

-40°C to +100°C, short-term up to +125°C

가 VAT 가 가 .

(22.07.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16



# EPIC® H-B 16 TGB

	Article description	M	PG	Neck	Packaging unit
H-B	:	(	,	)	
10081000	H-B 16 TGB 21	-	21	yes	5
19081000	H-B 16 TGB M25	25	-	-	5

(22.07.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16