


EPIC® H-BE 6 Screw termination

가

Made in Germany

가



Lapp



가

EPIC® H-BE

Railway applications

- Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL3

UL UL 508/UL 2237

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

EPIC® H-BE 6 Screw termination

/	
ETIM 5:	ETIM 5.0 Class-ID: EC000438 ETIM 5.0 class :
ETIM 6:	ETIM 6.0 Class-ID: EC000438 ETIM 6.0 Class-Description: Contact insert for industrial connectors
(V):	IEC: 500 VUL: 600 VCSA: 600 V
:	6 kV
(A):	IEC: 16 A UL: 16 A CSA: 16 A
:	3
:	UL94 V-0
:	< 2 mOhm
:	,
/ :	6 + PE
:	: 0.5 - 2.5 mm ²
(mm):	8
:	PC,
:	500
:	-40°C to +100°C, short-term up to +125°C

가 VAT 가 가 .



EPIC® H-BE 6 Screw termination

	Article description	Contact type			/ PU
H-BE 6					
10190000	EPIC® H-BE 6 SS		yes	1 - 6	10
10191000	EPIC® H-BE 6 BS		yes	1 - 6	10
10190100	EPIC® H-BE 6 SS		-	1 - 6	10
10191100	EPIC® H-BE 6 BS		-	1 - 6	10