

EPIC® MH 1 250A

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.

EPIC® MH 1 250A

250A



Lapp



e-



()
95mm²

(13.07.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

EPIC® MH 1 250A

PE

(PE)

Railway applications

- Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL3

/

ETIM 5:	ETIM 5.0 Class-ID: EC002312
ETIM 6:	ETIM 6.0 Class-ID: EC002312
(V):	1000 V AC/DC
:	8 kV
(A):	250
:	3
:	UL94 V-0
/ :	1
:	: 25mm ² ... 95mm ²
:	PA
:	500
:	-40°C ~ +120°C

가 VAT 가 가 .

(13.07.2024)



EPIC® MH 1 250A

	Article description	Contact type	Slots	Packaging unit
44423342	EPIC® MHS 1 CM 250A		2	10
44423328	EPIC® MHS 1 CM 250A protected		2	10
44423329	EPIC® MHB 1 CM 250A protected		2	10

(13.07.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16