

FLEXIMARK®

SQUIX

EOS5 *

FLEXIMARK®

SQUIX

EOS 5

300dpi

(: +4615577764, : support@fleximark.se)



(150 mm/)
: 300dpi

FLEXIMARK® 10.0

(, FLEXIMARK® , PUR TA)

EOS 5

FLEXIMARK® 10.0

FLEXIMARK® SQUIX EOS 5

Windows®

USB (1.8m)

(24.04.2024)



FLEXIMARK®

SQUIX EOS5 *

ETIM 5:	ETIM 5.0 Class-ID: EC001675
	ETIM 5.0 Class : / /MFC
ETIM 6:	ETIM 6.0 Class-ID: EC001675
	ETIM 6.0 Class : / /MFC
Dimensions:	SQUIX: 274x242x446 mm (HxWxD)
	EOS5: 245x264x412mm (x x)
:	Material thickness:
	0.03-0.60 mm (SQUIX)
	0.05-0.60 mm (EOS5)
	Carrier width:
	10-120 mm (SQUIX)
	10-116 mm (EOS5)
	Ø: 38.0-100.0mm (SQUIX) 38-76mm (EOS5)
:	500m (SQUIX) 360m (EOS5)
: 10/100 Mbit/s:	EOS5: Up to 150.00 mm/s
	SQUIX: Up to 300,00 mm/s
:	SQUIX: 9.0 kg
	EOS5: 5 kg
:	

*

가 VAT	가 가 .) LCK 32	640	640	1	PU
FLEXIMARK®						

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



FLEXIMARK®

SQUIX

EOSS *

		PU
83259532	FLEXIMARK® EOS5/300	1
83259602	FLEXIMARK® Thermoprinter SQUIX 4/300M	1
83259536	FLEXIMARK® EOS5	1
83259603	FLEXIMARK® Perforation cutter PCU400 SQUIX	1

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16