

ÖLFLEX® STATIC CY black

PVC

ÖLFLEX® STATIC CY BLACK - EMC

0,6/1kV

PVC

EMC
EMC-

가

NYN

- ÖLFLEX® CHAIN 809 SC CY 가



, / 12.5 x EMC 가 가 가 ,

(24.04.2024)

ÖLFLEX® STATIC CY black

IEC 60332-1-2

ISO 4892-2UV UV

DIN EN 50290-2-22(TM54)

: PVC

PVC-

ETIM 5:

ETIM 5.0 Class-ID: EC000057
ETIM 5.0

ETIM 6:

ETIM 6.0 Class-ID: EC000057
ETIM 6.0 Class :

:

VDE 0295 5/ IEC 60228 5

가 가

:

: 6 x

: 12.5 x

:

U0/U: 600/1000 V

:

Core/screen: 2000 V

:

: -40°C +80°C

: -30 °C ~ +70 °C

가 가 () 가
www.lappkabel.de/en/cable-standradlengths

: 30 kg, (e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



ÖLFLEX® STATIC CY black

Article number	(mm ²)	(mm)	(kg/km)	(kg/km)
4600023	16	10.3	177	275
4600024	25	12.7	267	396
4600025	35	14.3	384	542
4600026	50	16.9	537	752
4600027	70	18.7	763	1004
4600028	95	21.7	1012	1368
4600029	120	24.7	1264	1719

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16