

# NYM-J

NYM-J, VDE, PVC house wiring cable, or installation on or under the plaster, in masonry and concrete

CPR: [www.lappkabel.com/cpr](http://www.lappkabel.com/cpr)



, 가

: IEC 60332-1-2

VDE 0250 204

: PVC

PVC-

ETIM 5:

ETIM 5.0 Class-ID: EC000043  
ETIM 5.0

ETIM 6:

ETIM 6.0 Class-ID: EC000043  
ETIM 6.0 Class :

(24.04.2024)

# NYM-J

:	5	: VDE 0293-308	T9
:	6	:	
:		16mm <sup>2</sup> :	
:		: 4 x	
:		U0/U: 300/500 V	
:		2000 V	
:		J = GN/YE	
:		O = GN/YE	
:		: +5°C to +60°C	
:		: -40°C +70°C	

가 가 ( . ) 가 .  
www.lappkabel.de/en/cable-standradlengths  
: 30 kg or 250 m,  
(e.g. 1 x 500 m or 5 x 100 m ).  
가 VAT 가 가 .

Article number	(CORE) / (mm <sup>2</sup> )	(mm)	(kg/km)	(kg/km)
1600008	1 G 2,5	6	24	60
1600009	1 G 4	6.7	38	85
1600010	1 G 6	7.2	58	105
1600011	1 G 10	8.6	96	160
1600012	1 G 16	9.6	154	220
16000003	3 G 1,5	8.4	43	120
16000013	4 G 1,5	9.2	58	150
16000023	5 G 1,5	9.9	72	175
1600003	7 G 1,5	11.6	101	235
16000213	3 G 2,5	9.6	72	170
16000053	4 G 2,5	10.6	96	210
16000063	5 G 2,5	11.5	120	290
1600071	7 G 2,5	13.7	168	380
16010223	3 G 4	11.3	115	250
16000313	4 G 4	12.7	154	315
16000513	5 G 4	14	192	370
16010233	3 G 6	12.8	173	335
16000323	4 G 6	13.8	230	410
16000523	5 G 6	15.5	288	500
16000333	4 G 10	18	384	680
16000533	5 G 10	19.5	480	810
16000543	5 G 16	23	768	1200
16000353	4 G 25	26	960	1500
16000553	5 G 25	28	1200	1800

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16