

## ÖLFLEX® LIFT F

PVC FLAT

ÖLFLEX® LIFT F -PVC , U <sub>0</sub>/U: 300/500V, H07VVH6-F / H05VVH6-F



가

VDE 가 . 35m 1.6m/s ÖLFLEX® CRANE ÖLFLEX(R) LIFT АЗ

: IEC 60332-1-2

Based on EN 50214/ VDE 0283-2

: PVC

PVC-

(24.04.2024)

©2024 Lapp Group - all rights reserved. http://lappkorea.lappgroup.com data sheet

PN 0456 / 02\_03.16



## ÖLFLEX® LIFT F

```
ETIM 5:
                                                    ETIM 5.0 Class-ID: EC000825
                                                    ETIM 5.0
    ETIM 6:
                                                    ETIM 6.0 Class-ID: EC000825
                                                    ETIM 6.0 Class :
                                                             : VDE 0293-308
                                                                                                         T9
        :
                                                    U0/U 300/500 V
                                                                       , VDE 0295
                                                                                   5 IEC 60228 Cl. 5
                                                               가
                                                    U0/U 450/750 V
                                                                       , VDE 0295
                                                                                         6
                                                                                               IEC 60228
                                                          6
                                                                                                 10 mm<sup>2</sup> :
                                                                      5)
                                                              : 10 x
                                                        1.0 mm<sup>2</sup>: U0/U: 300/500 V
                                                    .5 mm<sup>2</sup> : U0/U: 450/750 V
                                                    3000 V
                                                    G = GN/YE
                                                    X = GN/YE
                                                                  1.0 mm<sup>2</sup>)
                                                    0°C ~ +70°C (
                                                    -15 °C ~ +70°C (1.5 mm<sup>2</sup> )
                                         가
                                                                         ( . )
                                                                                                  가
                  www.lappkabel.de/en/cable-standradlengths
                30 kg or 250 m,
                               . (e.g. 1 x 500 m
                                                    or 5 x 100 m
가
      VAT
                    가
                           가 .
```

(24.04.2024)

©2024 Lapp Group - all rights reserved. http://lappkorea.lappgroup.com data sheet PN 0456 / 02\_03.16

	(CORE) / (mm²)	, x (mm)	(kg/km)	(kg/km)
ÖLFLEX® LIFT F				
U0/U: 300/500 V,	: 0°C ~ +70°C		T	T
0042020	12.0 G 1.0	36 x 4.7	115	392
0042021	16.0 G 1.0	48.5 x 4.7	153.6	521
0042022	20.0 G 1.0	59 x 4.7	192	645
0042023	24.0 G 1.0	71.5 x 4.7	230	772
U0/U: 450/750 V, :-15°C ~ +70°C				
00420013	4.0 G 1.5	15.5 x 5.2	57.6	132
00420023	5.0 G 1.5	19.7 x 5.2	72	170
0042003	7.0 G 1.5	27 x 5.2	100.8	236
0042004	8.0 G 1.5	29 x 5.2	115	266
0042005	10.0 G 1.5	36.5 x 5.2	144	333
0042006	12.0 G 1.5	42 x 5.2	172.8	422
00420073	4.0 G 2.5	19 x 5.9	96	206
00420083	5.0 G 2.5	24 x 5.9	120	257
0042009	7.0 G 2.5	32.5 x 5.9	168	345
0042010	8.0 G 2.5	35 x 5.9	192	390
0042050	12.0 G 2.5	52.5 x 5.9	288	580
00420113	4.0 G 4.0	21 x 6.8	153.6	343
0042012	7.0 G 4.0	38 x 6.8	268.8	589
00420133	4.0 G 6.0	24 x 7.3	230	425
00420143	4.0 G 10.0	30.5 x 9.5	384	709
00420153	4.0 G 16.0	35 x 10.8	614	1015
00420163	4.0 G 25.0	42 x 13	960	1366

