

ÖLFLEX® HEAT 260 C MC

PTFE

ÖLFLEX® HEAT 260 C MC - PTFE

, -190°C ~ +260°C

EMC



(24.04.2024)

ÖLFLEX® HEAT 260 C MC



가

가
ÖLFLEX® HEAT 260

-
-
-
-
-
-가
-
-

EMC
ÖLFLEX® HEAT 260

PTFE

- , , , , ,
-
-
-
-
-
-
-
-
-

PTFE-

PTFE- ,

ÖLFLEX® HEAT 260 C MC

ETIM 5:	ETIM 5.0 Class-ID: EC001578
	ETIM 5.0 Class 가
ETIM 6:	ETIM 6.0 Class-ID: EC001578
	ETIM 6.0 Class :
:	VDE 0293-308 , T9
:	VDE 0295 5/ IEC 60228 5
:	가 가
:	: 15 x
:	: 4 x
:	U0/U: 300/500 V
:	C/C: 2500 V
:	C/S: 2000 V
:	G = GN/YE
:	X = GN/YE
:	:
:	-190°C +260°C
:	: +300°C

가 가 (.) 가 .
www.lappkabel.de/en/cable-standradlengths
 : 30 kg or 250 m,
 . (e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .



ÖLFLEX® HEAT 260 C MC

	(CORE) / (mm ²)	(mm)	(kg/km)	(kg/km)
ÖLFLEX® HEAT 260 C MC				
0091330	3 G 0.75	5.5	46	75
0091331	4 G 0.75	5.9	51	87
0091332	3 G 1.0	5.8	48	81
0091333	4 G 1.0	6.4	65	104
0091334	3 G 1.5	6.3	65	101
0091335	4 G 1.5	7.2	86	134
0091336	5 G 1.5	7.8	105	162
0091337	3 G 2.5	7.9	114	160
0091338	4 G 2.5	8.7	140	204
0091339	5 G 2.5	9.4	209	270

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16