



ÖLFLEX® 450 P

가

ÖLFLEX® 450 P -

가

PUR / PVC

PVC/PUR



가

가

가

: IEC 60332-1-2

가

(25.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

ÖLFLEX® 450 P

VDE 0250 / 0285

: PVC
: PVC -
: PUR -

ETIM 5:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class 가
ETIM 6:	ETIM 6.0 Class-ID: EC001578 ETIM 6.0 Class :
:	VDE 0293-308 , T9
:	IEC 60228/VDE 0295 class 5
:	: 15 x : 4 x
:	U0/U: 300/500 V
:	3000 V
:	G = GN/YE X = GN/YE
:	: -5°C ~ +70°C : -40°C +80°C

, 가 가 . (.) 가 .
: www.lappkabel.de/en/cable-standradlengths
30 kg or 250 m,
(e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .



ÖLFLEX® 450 P

Article number	(CORE) / (mm ²)	(mm)	(kg/km)	(kg/km)
ÖLFLEX® 450 P				
0012101	2 X 1.0	8	19.2	82
0012102	3 G 1.0	8.4	29	89
0012202	3 G 1.5	9.3	43	120
00122033	4 G 1.5	10.1	58	160
00122043	5 G 1.5	10.9	72	179
0012302	3 G 2.5	10.8	72	186
00123043	5 G 2.5	13.6	120	283

(25.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16