

NSHXAFÖ 1,8/3 kV

NSHXAFÖ 1,8/3 kV AC, VDE , , , Class 5,



VDE 0250 Part 606 , U0/U: 1.8/3 kV
VDE 0298 Part 3 , 1000V

NSHXAF VDE 0100 Part 520

, , ,
, ; 1000V
, , ,
가 ,

:
: IEC 60332-1-2 가
3.6/6 kVac 가

<VDE> NSHXAFÖ VDE 0250-606 1,8/3 kV

NSHXAFÖ 1,8/3 kV

: 3GI3
: , HM3

ETIM 5: ETIM 5.0 Class-ID: EC000993
ETIM 5.0 Class :
ETIM 6: ETIM 6.0 Class-ID: EC000993
ETIM 6.0 Class :
: VDE 0295 5/ IEC 60228 5
가 가
: : 10 x
: 6 x
: U0/U: 1.8/3 kV
: 6000 V
: During laying: -25 up to +70°C
: Fixed installation: -40°C up to +90°C

가 가 (.) 가 .
www.lappkabel.de/en/cable-standradlengths
: 30 kg or 250 m,
(e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .

(24.04.2024)



NSHXAFÖ 1,8/3 KV

Article number	(mm ²)	(mm)	(kg/km)	(kg/km)
3022673	1.5	7	14.4	60
3022674	2.5	7.5	24	70
3022675	4	9	38.4	90
3022676	6	9.5	57.6	120
3022677	10	11	96	180
3022678	16	13	153.6	250
3022679	25	15	240	390
3022680	35	16.5	336	470
3022681	50	18	480	625
3022682	70	20.5	672	880
3022683	95	24	912	1190
3022684	120	26	1152	1430
3022685	150	28	1440	1750
3022686	185	31	1776	2160
3022687	240	34.5	2304	2718
3022688	300	38	2880	3470

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16