

ÖLFLEX® SPIRAL 540 P with angular, isolated ground plug

가

ÖLFLEX® SPIRAL 540 P

-

PUR

,



CE UK CA



3.5

가

PUR

,

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

ÖLFLEX® SPIRAL 540 P with angular, isolated ground plug

-30°C
16-A , IP 20

Stecker: DIN VDE 620-1/Normblatt DIN 49441 R2

: ÖLFLEX® SPIRAL 540 P, ÖLFLEX® 540 P

: TPE

2- , : = 가 - 200 mm , = 30mm 60mm

ETIM 5:

ETIM 5.0 Class-ID: EC000247
ETIM 5.0 Class :

ETIM 6:

ETIM 6.0 Class-ID: EC000247
ETIM 6.0 Class-Description: Spiralized cable

:

가 HD 308/VDE 0293-308: 3-

:

VDE 0295 5/ IEC 60228 5
가 가

:

U0: 250 V AC

:

2000 V

:

G = GN/YE

:

: -30°C +50°C

가 , 가 가 (.) 가 .

가 VAT
LAPP
가
DIN VDE 0620-1
E: "

가 가 . (VDE)

. 가 " - 1: ,



ÖLFLEX® SPIRAL 540 P with angular, isolated ground plug

	(CORE) / (mm ²)	, (mm)	, (mm)	(mm)	(mm)
73220852	3 G 0.75	1000	300	7	24
73220853	3 G 0.75	2000	600	7	24
73220854	3 G 0.75	3500	1000	7	24
73220855	3 G 1.0	1000	300	7.4	29
73220856	3 G 1.0	2000	600	7.4	29
73220863	3 G 1.0	3500	1000	7.4	29
73220860	3 G 1.5	1000	300	8.9	32
73220861	3 G 1.5	2000	600	8.9	32
73220862	3 G 1.5	3500	1000	8.9	32

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16