

# ÖLFLEX® CHAIN 819 CP

PVC

ÖLFLEX® CHAIN 819 CP - PVC

PU-

- 가  
UL/cUL



가  
, 가

(23.04.2024)

# ÖLFLEX® CHAIN 819 CP

EMC-

Indoor applications or dry rooms

IEC/EN: 60332-1-2  
UL/CSA: , FT2

EMC-

: UL AWM Style 21576  
: cUL AWM Style I/II A FT2  
UL File No. E63634  
: 가 T3

: PVC

Lapp-PU-Special Blend ( , RAL 9005)

ETIM 5:

ETIM 5.0 Class-ID: EC000104  
ETIM 5.0

Black with white numbers acc. to VDE 0293-334

VDE 0295 5/ IEC 60228 5  
가 가

Flexing: up from 10 x outer diameter  
: 4 x

IEC U0/U: 300/500 V  
UL: 1,000V

Core/core: 4000 V  
Core/screen: 2000 V

G = GN/YE  
X = GN/YE

: -5°C ~ +70°C (UL: +80°C)  
: -40°C ~ +70°C(UL: +80°C)

A2-1

(23.04.2024)



# ÖLFLEX® CHAIN 819 CP

www.lappkabel.de/en/cable-standradlengths ( : ) 가  
: 30 kg or 250 m,  
(e.g. 1 x 500 m or 5 x 100 m ).  
가 VAT 가 가 .

# ÖLFLEX® CHAIN 819 CP

| Article number | (CORE) / (mm <sup>2</sup> ) | (mm) | (kg/km) | (kg/km) |
|----------------|-----------------------------|------|---------|---------|
| 1027900        | 2 X 0.5                     | 5.8  | 22.5    | 42.9    |
| 1027901        | 3 G 0.5                     | 6.1  | 27.1    | 50.6    |
| 1027902        | 4 G 0.5                     | 6.6  | 35.1    | 62.6    |
| 1027903        | 5 G 0.5                     | 7.1  | 43.1    | 74.7    |
| 1027904        | 7 G 0.5                     | 8.5  | 55.8    | 101     |
| 1027905        | 12 G 0.5                    | 10   | 83.1    | 144.5   |
| 1027906        | 18 G 0.5                    | 11.8 | 120     | 207.1   |
| 1027907        | 25 G 0.5                    | 14.1 | 171     | 288.6   |
| 1027910        | 2 X 0.75                    | 6.2  | 30.4    | 52.7    |
| 1027911        | 3 G 0.75                    | 6.6  | 37.5    | 63.4    |
| 1027912        | 4 G 0.75                    | 7.1  | 47.9    | 78      |
| 1027913        | 5 G 0.75                    | 7.7  | 55.2    | 90.4    |
| 1027914        | 7 G 0.75                    | 9.1  | 75.9    | 126.1   |
| 1027915        | 12 G 0.75                   | 10.9 | 115.3   | 183.6   |
| 1027916        | 18 G 0.75                   | 13   | 168     | 269.8   |
| 1027917        | 25 G 0.75                   | 15.6 | 239.6   | 377     |
| 1027920        | 2 X 1.0                     | 6.5  | 35.3    | 58.5    |
| 1027921        | 3 G 1.0                     | 6.9  | 44.7    | 71.6    |
| 1027922        | 4 G 1.0                     | 7.5  | 57.7    | 89.4    |
| 1027923        | 5 G 1.0                     | 8.3  | 70.3    | 110.2   |
| 1027924        | 7 G 1.0                     | 9.8  | 92.7    | 149.2   |
| 1027925        | 12 G 1.0                    | 11.7 | 148.7   | 224.4   |
| 1027926        | 18 G 1.0                    | 14   | 224.1   | 331.3   |
| 1027927        | 25 G 1.0                    | 16.7 | 299.5   | 449.2   |
| 1027930        | 2 X 1.5                     | 7.1  | 47.9    | 73.8    |
| 1027931        | 3 G 1.5                     | 7.5  | 62.5    | 92.6    |
| 1027932        | 4 G 1.5                     | 8.4  | 80      | 118.9   |
| 1027933        | 5 G 1.5                     | 9.1  | 97.5    | 142.7   |
| 1027934        | 7 G 1.5                     | 10.9 | 129.7   | 194.9   |
| 1027935        | 12 G 1.5                    | 13.3 | 211     | 301.9   |
| 1027936        | 18 G 1.5                    | 15.7 | 319     | 447.8   |
| 1027937        | 25 G 1.5                    | 18.7 | 428.1   | 606.5   |
| 1027940        | 3 G 2.5                     | 9    | 97.4    | 138.9   |
| 1027941        | 4 G 2.5                     | 10.1 | 124.8   | 178.2   |

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16



# ÖLFLEX® CHAIN 819 CP

| Article number | (CORE) / (mm <sup>2</sup> ) | (mm) | (kg/km) | (kg/km) |
|----------------|-----------------------------|------|---------|---------|
| 1027944        | 5 G 2.5                     | 11.2 | 148.7   | 215.4   |
| 1027942        | 7 G 2.5                     | 13.5 | 206.5   | 301.6   |
| 1027943        | 12 G 2.5                    | 16.2 | 347.5   | 478.5   |
| 1027950        | 4 G 4.0                     | 11.9 | 187     | 256.1   |
| 1027952        | 4 G 10.0                    | 18.2 | 452.1   | 606.5   |
| 1027955        | 4 G 16.0                    | 21.3 | 699.5   | 884.2   |
| 1027957        | 4 G 25.0                    | 26.3 | 1,062.1 | 1,349.7 |

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16