

ÖLFLEX® ROBUST FD

TPE -

ÖLFLEX® ROBUST FD -

- 가

Good chemical resistance please see Appendix T1

LAND MAREL CTURO ANT OLE EVE DODUCT ED















가 , UV

가

- ,

(19.05.2025)

©2025 Lapp Group - all rights reserved. http://lappkorea.lappgroup.com data sheet

PN 0456 / 02_03.16



ÖLFLEX® ROBUST FD

```
/UV
EN 50396 HD 605 S2
                        가
      , -40°C
Norm references / Approvals
VDE 0250 / 0285
                      가
                                           T3
        : TPE
          TPE,
                    (RAL 9005)
    ETIM 5:
                                                   ETIM 5.0 Class-ID: EC000104
                                                   ETIM 5.0
    ETIM 6:
                                                   ETIM 6.0 Class-ID: EC000104
                                                   ETIM 6.0 Class
                                                   Black cores with printed white numbers (VDE 0293-334)
                                                   VDE 0295 class 6, IEC 60228 class 6
                                                                                                   가
        :
                                                  7.5 x
                                                   (< 70 °C)
                                                  10 x
                                                       105 °C)
                                                           : 4 x
                                                   U0/U: 300/500 V
                                                                       A2-1
                                                   4000 V
                                                  G = GN/YE
                                                  X = GN/YE
                                                        : -40°C ~ +105°C
                                                           : -50°C ~ +105°C
```

(19.05.2025) ©2025 Lapp Group - all rights reserved. http://lappkorea.lappgroup.com

data sheet PN 0456 / 02_03.16



ÖLFLEX® ROBUST FD

, (:) 가 www.lappkabel.de/en/cable-standradlengths : 30 kg or 250 m, . (e.g. 1 x 500 m or 5 x 100 m). 가 VAT 가 가 .

(19.05.2025)
©2025 Lapp Group - all rights reserved.
http://lappkorea.lappgroup.com
data sheet
PN 0456 / 02_03.16

11.8

4 G 2.5

0026531

96

181

ÖLFLEX® ROBUST FD

Article number	(CORE) / (mm²)	(mm)	(kg/km)	Weight (kg/km)
0026532	5 G 2.5	12.9	120	228
0026533	7 G 2.5	15.7	168	329
0026534	12 G 2.5	18.7	288	491
0026541	4 G 4.0	13.8	153.6	261
0026551	4 G 6.0	14.8	230.4	356
0026561	4 G 10.0	20.1	384	596
0026571	4 G 16.0	23.8	614.4	910

