



ÖLFLEX® SERVO FD 781 CY

PVC

ÖLFLEX® SERVO FD 781 CY -

EMC- - 가 가



(,)

UV- , , 가

(25.04.2024)

ÖLFLEX® SERVO FD 781 CY

IEC 60332-1-2

VDE 0250 / 0285

: 가 T3

(class 6)
: (PP)
()

(RAL 2003) PVC

ETIM 5:

ETIM 5.0 Class-ID: EC000104
ETIM 5.0

ETIM 6:

ETIM 6.0 Class-ID: EC000104
ETIM 6.0 Class :

: Black with white numbers acc. to VDE 0293-334
: VDE 0295 class 6, IEC 60228 class 6 가

: : 7.5 x
: 4 x

: U0/U: 600/1000 V

: Core/Core: 4 kV
Core/Screen: 4 kV

: G = gn-ye 가

: : -5°C +70°C
: -40°C +80°C

: A2-1

: (:) 가

: www.lappkabel.de/en/cable-standradlengths

: 30 kg or 250 m,
(e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .

(25.04.2024)



ÖLFLEX® SERVO FD 781 CY

Article number	(CORE) / (mm ²)	(mm)	(kg/km)	(kg/km)
ÖLFLEX® SERVO FD 781 CY				
0036320	4 G 1.5	9.8	89	157
0036321	4 G 2.5	11.9	133.8	233
0036322	4 G 4.0	13.5	210.9	335
0036324	4 G 10.0	19.7	488.2	747
0036325	4 G 16.0	23.9	744.8	1109
0036327	4 G 35.0	33.3	1,565.4	2264
0036328	4 G 50.0	38.3	2,174.9	3090

(25.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16