

ÖLFLEX® CHAIN 809 CY

PVC

PVC

-

ÖLFLEX® CHAIN 809 CY - UL/cUL AWM

-

가

AWM

EMC



가 , 가

, 가

(,)

EMC-

,

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



ÖLFLEX® CHAIN 809 CY

‘ ‘ ‘

WTG()

:

UL/CSA: VW-1, FT1.

IEC/EN: 60332-1-2

EMC-

UL AWM Style 20886

cUL AWM II A/B FT1

UL File No. E63634

:

가

T3

: PVC

(RAL 7001) PVC

ETIM 5:

ETIM 5.0 Class-ID: EC000104

ETIM 5.0

ETIM 6:

ETIM 6.0 Class-ID: EC000104

ETIM 6.0 Class :

Black with white numbers acc. to VDE 0293-334

VDE 0295 5/ IEC 60228 5

가 가

WTG :

TW-0 & TW-1, T0

Flexing: up from 10 x outer diameter

: 4 x

VDE: U0/U: 300/500 V

UL & CSA: 1000 V

Core/core: 4000 V

Core/screen: 2000 V

G = GN/YE

X = GN/YE

: VDE 0 °C +70 °C (UL/CSA: +80°C)

: VDE -40 °C +70 °C; (UL/CSA +80°C)

A2-1

(:) 가

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

ÖLFLEX® CHAIN 809 CY

www.lappkabel.de/en/cable-standradlengths
: 100 m; (500; 1000) m

가 VAT 가 가 .

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

ÖLFLEX® CHAIN 809 CY

Article number	(CORE) / (mm ²)	(mm)	(kg/km)	(kg/km)
ÖLFLEX® CHAIN 809 CY				
1026751	2 X 0.5	5.8	36	45
1026752	3 G 0.5	6.1	43	59
1026753	4 G 0.5	6.6	49	83
1026754	5 G 0.5	7.1	57	96
1026755	7 G 0.5	8.5	69	136
1026756	12 G 0.5	10	104	200
1026757	18 G 0.5	11.8	141	275
1026758	25 G 0.5	14.1	211	350
1026759	2 X 0.75	6.2	43	56
1026760	3 G 0.75	6.6	52	70
1026761	4 G 0.75	7.1	61	95
1026762	5 G 0.75	7.7	72	130
1026763	7 G 0.75	9.1	89	168
1026764	12 G 0.75	10.9	138	232
1026765	18 G 0.75	13	211	315
1026766	25 G 0.75	15.6	280	435
1026767	2 X 1.0	6.5	51	84
1026768	3 G 1.0	6.9	62	110
1026769	4 G 1.0	7.5	74	130
1026770	5 G 1.0	8.3	88	156
1026771	7 G 1.0	9.8	112	192
1026772	12 G 1.0	11.7	185	285
1026773	18 G 1.0	14	268	395
1026774	25 G 1.0	16.7	354	486
1026775	2 X 1.5	7.1	65	97
1026776	3 G 1.5	7.5	82	125
1026777	4 G 1.5	8.4	100	165
1026778	5 G 1.5	9.1	119	193
1026779	7 G 1.5	10.9	154	245
1026780	12 G 1.5	13.3	268	365
1026781	18 G 1.5	15.7	373	553
1026782	25 G 1.5	18.7	530	734
1026783	3 G 2.5	9	118	188



ÖLFLEX® CHAIN 809 CY

Article number	(CORE) / (mm ²)	(mm)	(kg/km)	(kg/km)
1026784	4 G 2.5	10.1	147	236
1026785	7 G 2.5	13.5	253	340
1026788	4 G 4.0	11.9	248	305