

ÖLFLEX® ROBOT F1 (C)

PUR , UL/cUL AWM

ÖLFLEX® ROBOT F1 (C) - UL/cUL AWM

+/- 180 °/m
AWM



Lapp



(23.04.2024)

ÖLFLEX® ROBOT F1 (C)

:	가
:	± 180 °/m
:	: 10 x
:	: 4 x
:	IEC: up to 0.34 mm ² 250 Vss.
:	0.5 - 2.5 mm ² U0/U 300/500 V
:	UL/CSA: up to 1.5 mm ² 600 V,
:	from 2.5 mm ² 1000 V
:	0.34 mm ² : 1500 V
:	0.5 mm ² : 2000 V
:	G = GN/YE
:	X = GN/YE
:	: -40°C +80°C
:	: -50°C +80°C

(:) 가
www.lappkabel.de/en/cable-standradlengths
 : 30 kg or 250 m,
 . (e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .

(23.04.2024)

ÖLFLEX® ROBOT F1 (C)

Article number	(CORE) / (mm ²)	(mm)	(kg/km)	(kg/km)
0029653	3 x 2 x 0,25	8.0	38	100
0029654	25 x 0,25	13.8	115	280
0029655	2 x 0,34	5.2	18	54
0029656	3 x 0,34	5.4	20	56
0029657	4 x 0,34	6.6	28	72
0029658	5 x 2 x 0,34	10.2	69	158
0029689	12 G 1,5	15.4	230	380
0029690	18 G 1,5	18.5	340	550
0029664	4 G 1,5	8.8	75.1	120
0029665	4 G 2,5	10.3	116	200
0029691	4 G 1,5 + (2 x 1,0)	11.0	116	213
0029692	4 G 2,5 + (2 x 1,0)	12.0	150	270

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16