

ÖLFLEX® ROBOT 900 DP

PUR

ÖLFLEX® ROBOT 900 DP -

+/- 180 °/m



Lapp



(24.04.2024)

ÖLFLEX® ROBOT 900 DP



PUR

500

: 가 T3
For travel distances up to 10 m

: TPE

PTFE

(DP): -
, (RAL 9005)

ETIM 5:

ETIM 5.0 Class-ID: EC000104
ETIM 5.0

ETIM 6:

ETIM 6.0 Class-ID: EC000104
ETIM 6.0 Class :

:

0.34 mm²: DIN 47100

0.5 mm² :

:

C/C approx. 100 nF/km
C/S approx. 120 nF/km

:

0.7 mH/km

:

(24.04.2024)

ÖLFLEX® ROBOT 900 DP

: $\pm 180^\circ/\text{m}$
 : () : 15 x
 : : 4 x
 : 0,34 mm²: 48 V AC
 : 0.5 mm² U0/U :: 300/500 V
 : 0.34 mm²: 1500 V
 : 0.5 mm² : 3000 V
 : G = GN/YE
 : X = GN/YE
 : : -40°C +80°C
 : : -50°C +80°C

, (:) 가
 : www.lappkabel.de/en/cable-standradlengths
 : 30 kg or 250 m,
 . (e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .

(24.04.2024)



ÖLFLEX® ROBOT 900 DP

| Article number | (CORE) / (mm ²) | (mm) | (kg/km) | (kg/km) |
|----------------|-----------------------------|------|---------|---------|
| 0028100 | 12 x 0,14 | 6.7 | 42.5 | 69 |
| 0028105 | 3 x 2 x 0,14 | 6.2 | 17 | 44 |
| 0028126 | 25 x 0,25 | 11.1 | 103.5 | 183 |
| 0028135 | 4 x 0,34 | 5.7 | 21.3 | 46 |
| 0028136 | 5 x 2 x 0,34 | 9.1 | 64.4 | 114 |
| 0028195 | 12 G 1,5 | 14.0 | 259 | 395 |

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16