

ÖLFLEX® SOLAR XLS-R T

가

PV



가

가

가 PV

PV

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

ÖLFLEX® SOLAR XLS-R T

HD 605/A1 /UV-
EN 50396

XLS-R T= X-Linked Standard-Reduced Twin
E-beam 가

:

ETIM 5:

ETIM 5.0 Class-ID: EC001578

ETIM 5.0 Class 가

:

/
/

:

IEC 60228/VDE 0295 class 5

:

: 5 x

:

AC U0/U: 600/1000V

DC U0/U: 900/1500V

:

DC 1.8kV(- ,)

:

AC 6500 V

:

: -40°C ~ +100°C()

가 가 (.) 가 .
www.lappkabel.de/en/cable-standradlengths

: 100 m; (500; 1000) m

가 VAT 가 가 .

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



ÖLFLEX® SOLAR XLS-R T

	(CORE) / (mm ²)	, x (mm)	(kg/km)	(kg/km)
0023984	2 X 4	10.7 x 5.2	76.8	128

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16