


ÖLFLEX® TRAIN HT 150 FF 3,6kV

Single-core cable according to EN 50382-2 type FF for high requirements in railway applications

ÖLFLEX® TRAIN HT 150 FF 3.6kV - EN 50382-2 FF , 3.6/6kV, 150°C, / , EN 45545: HL1-HL3

Meets EN 50382-2 type FF and EN 45545-2

High temperature resistance: -40°C up to +150°C



(23.04.2024)

ÖLFLEX® TRAIN HT 150 FF 3,6kV

Good chemical resistance please see Appendix T1

For high ambient temperatures

Reduced flame spreading increases the protection against damage to persons and property in the event of a fire

EN / IEC 가 :- EN 60754-1 .- EN 60754-2 가 가 .- EN 60684-2
 가 .- EN 50305 가 가 .- EN 61034-2 .- EN 60332-1-2 .-
 EN 60332-3-24 / EN 60332-3-25 / EN 50305 .
 :- EN 50382-2 - EN 50382-2 - EN 50382-2 - EN 50382-2

EN 50355 , A

EN 50264-3-1 Typ MM
 EN 45545-2 HL1, HL2, HL3

Insulation: Silicone rubber compound, type EI 111
 : ()
 Outer sheath: Silicone rubber compound, type EM 107
 :

ETIM 5:	ETIM 5.0 Class-ID: EC000057
:	ETIM 5.0
:	VDE 0295 5/ IEC 60228 5
:	가 가
:	: 3 x
:	: 5 x
:	U ₀ /U AC 3,6/6 kV
:	U _m AC 7,2 kV
:	V ₀ DC 5,4 kV
:	11 kV AC; 26 kV DC
:	-40°C ~ +150°C

가 VAT 가 가 . (.) 가 .
 : 30 kg or 250 m, 가 가 . (e.g. 1 x 500 m or 5 x 100 m).



ÖLFLEX® TRAIN HT 150 FF 3,6KV

Article number	(CORE) / (mm ²)	(mm)	(kg/km)	(kg/km)
15382060	1 X 2.5	10.8	24	122
15382061	1 X 4.0	11.3	38.4	143
15382062	1 X 6.0	11.9	57.6	167
15382063	1 X 10.0	12.8	96	217
15382064	1 X 16.0	13.9	153.6	291
15382065	1 X 25.0	16.0	240	403
15382066	1 X 35.0	17.3	336	503
15382067	1 X 50.0	19.0	480	668
15382068	1 X 70.0	20.8	672	867
15382069	1 X 95.0	22.6	912	1110
15382070	1 X 120.0	24.3	1152	1343
15382071	1 X 150.0	26.2	1440	1621
15382072	1 X 185.0	28.7	1776	2004
15382073	1 X 240.0	31.9	2304	2555

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16