



ÖLFLEX® CLASSIC 110 ORANGE

ÖLFLEX® CLASSIC 110 ORANGE - PVC
YSLY YY

가

CPR: www.lappkabel.com/cpr
EN 60204-1



4kV

EN 60204-1 (VDE 0113-1)

WTG()

: IEC 60332-1-2

IEC 60227-5 EN 50525-2-51

(25.04.2024)

ÖLFLEX® CLASSIC 110 ORANGE

PVC LAPP P8/1 가
 : PVC, (RAL2003)

ETIM 5: ETIM 5.0 Class-ID: EC000104
 ETIM 5.0

ETIM 6: ETIM 6.0 Class-ID: EC000104
 ETIM 6.0 Class :

: 가
 : IEC 60228/VDE 0295 class 5

WTG : TW-0 & TW-1, T0

: : 15 x
 : 4 x

: U0/U: 300/500 V

: 4000 V

: G = GN/YE

: X = GN/YE

: : -5°C ~ +70°C

: : -40°C +80°C

, 가 가 . (.) 가 .
 : www.lappkabel.de/en/cable-standradlengths
 30 kg or 250 m,
 . (e.g. 1 x 500 m or 5 x 100 m).

가 VAT 가 가 .



ÖLFLEX® CLASSIC 110 ORANGE

Article number	(CORE) / (mm ²)	(mm)	(kg/km)	(kg/km)
ÖLFLEX® CLASSIC 110 ORANGE				
0019700	2 X 1.0	5.7	19.2	53
0019701	3 G 1.0	6	28.8	65
0019702	3 X 1.0	6	28.8	65
0019706	4 G 1.0	6.5	38.4	80
0019708	4 X 1.0	6.5	38.4	80
0019709	5 G 1.0	7.1	50	95
0019710	2 X 1.5	6.3	29	68
0019711	3 G 1.5	6.7	43	85
0019718	4 G 1.5	7.2	58	105
0019720	5 G 1.5	8.1	72	128

(25.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16